

BLIND TEMPERATURE CONTROLLERS ——— C48S, ELEKTRA II, C961



C48S



ELEKTRA II



C961

- Ranges covering 0 to 1200 °C
- Inputs : J, K thermocouples, Pt100
- Time-proportioning or ONOFF control
- 5-LED solid state deviation indicator

MODEL	DEVIATION INDICATOR	SIZE (mm)	MOUNTING
C48S	Solid state, 5 LED	48x48x100	Panel, 44x44 mm cutout
C48S	Solid state, 5 LED	48x48x110	DIN Rail, 11-pin socket
ELEKTRA II	Solid state, 5 LED	72x72x113	Panel, 68x68 mm cutout
C961	Solid state, 5 LED	96x96x120	Panel, 92x92 mm cutout

SPECIFICATIONS

Input	See Table 1	Proportional cycle time	25 sec
Range	See Table 1	Output	1 x relay changeover contacts (NO-C-NC)
Resolution	See Table 1	Relay contact rating	6A/230 V AC, resistive
Setting accuracy	± 1% of full scale	Operating ambient temperature	5~45 °C
Control accuracy (ONOFF)	± 1% of full scale	Supply Voltage	230 V AC ± 10%, 50 hz
Proportional band	± 3 °C centred at set point		

TABLE 1

SENSOR	RANGE (°C)	SCALE RESOLUTION (°C)
Iron / Constantan (J)	0 to 400	5
Chromel / Alumel (K)	0 to 1200	15
Pt100	0 to 400	5

Note : Non-standard ranges can be supplied. Minimum order quantity applies.

radix
AN ISO 9001:2000 COMPANY

SALES INQUIRIES

1800-22-radix
1800-22-7234

www.radix.co.in

Radix Electrosystems Pvt Ltd
B-14, 2nd Floor, Ghanshyam Indl Estate
Veera Desai Road, Andheri (W)
Mumbai - 400 053, India
Tel : + 91 22 26730101 Fax : + 91 22 26731891
Email : sales@radix.co.in www.radix.co.in

BANGALORE C : 0-9341063830
BARODA C : 0-9376215882
CHANDIGARH C : 0-9316460869
CHENNAI C : 0-9381056345
CHHATISGARH C : 0-9329418246
COIMBATORE C : 0-9380284497
GOA C : 0-9371439090

GWALIOR C : 0-9329126120
HP C : 0-9316460869
HYDERABAD C : 0-9391053480
INDORE C : 0-9301995060
KARNATAKA C : 0-9341063831
KERALA C : 0-9341273814
NAGPUR C : 0-9322245543

NEW DELHI C : 0-9312600076
T : 011-25786350
ORISSA C : 0-9337002344
PUNE C : 0-9371113404
T : 020-24479759
PUNJAB C : 0-9316460869