


SOCKET WELD, LEAKPROOF



Standard Material : SS304 / SS316

SC : 1/2" BSP/NPSM

U : 50 / 100 / 150... upto 1200mm

Bore : 6.5mm for 6mm dia sensors

D1 : 16mm & 19mm

D2 : 13mm to 16mm, to be specified

Specify 'U'

Other threads, lengths, sizes, materials on request

ORDER CODE

TBR303 - C - 16 - 13 - 6.5 - 100 - 145 - G12 - X

MODEL _____
WELL MATERIAL

CODE	MATERIAL
A	SS304
B	Inconel 600
B1	Inconel 601
B4	Inconel 690
C	SS316
CL	SS316L
D	SS310
E	SS446
F	Carboon steel
BR	Brass
Q	Monel
T	Titanium
U6	Hastalloy C276
U2	Hastalloy C22
X	Other Materials

SHANK OD 'D1' _____

TAPERED END OD 'D2' _____

BORE _____

OTHER

PROCESS CONNECTION

CODE	THREAD
G14	1/4" BSPP
G12	1/2" BSPP
G34	3/4" BSPP
G25	1" BSPP
G38	1 1/2" BSPP
R12	1/2" BSPT
R34	3/4" BSPT
N14	1/4" NPT/NPSM
N12	1/2" NPT/NPSM
N34	3/4" NPT/NPSM
N25	1" NPT/NPSM
N38	1 1/2" NPT/NPSM
M20	M20 x 2.5
M27	M27 x 2
M33	M33 x 2

TOTAL LENGTH 'L' _____

INSERTION LENGTH 'U' _____

Abbreviations : SC - Sensor Connection, LE - Lag Extension, L - Total Length, U - Insertion Length, D1 - Major Diameter, D2 - Minor Diameter

All dimensions are in mm, unless otherwise specified.



Tel : +91 22 41929999 / 42537777

Email : sensors@radix.co.in • www.radix.co.in